



## FRESH-LOCK® Style 142 Soft Seal® ME Zipper Unique Double Zipper Design with sealant ribs

- Available in Presto's proprietary Soft Seal® material for a high-integrity side seal using less crushing energy.
- Requires less crushing time and/or temperature, allowing faster converting cycles.
- Easy-to-crush material creates high-quality side seals that won't leak, gap or distort.
- Double lock design helps keep product inside package fresh.
- Improved seal integrity minimizes leakage.
- Patented sealant ribs allow lower sealing temperatures that reduce film distortion for improved package appearance.
- Style 142 is available with either clear or colored locks.

### Double Zippers' double lock design helps keep your product fresh.

The FRESH-LOCK® Zipper style 142 made with our Soft Seal® material and special sealant ribs offers an unique double lock design for your package. The double locks are available in clear or colored. The Soft Seal® material provides easier edge crush and the special sealant ribs lowers sealing temperatures with less film distortion.

## Zipper Specification

### Product Description:

### STYLE 142 - Soft Seal® Material + ME Sealant

GKL07460-1

Medium Reusable Spool

GKL07461-1

Large Reusable Spool

#### PROFILE WEIGHT:

2.5 grams/ft +/- 0.1 grams/ft

#### WIDTH MEASUREMENTS:

14.0 mm +/- 0.5 mm

#### FOOTAGE/SPOOL:

Medium Spool: 8,000 ft + 100 - 0 ft  
Large Spool: 12,000 ft + 100 - 0 ft

#### SPOOLS/PALLET:

Medium Spool: 12 spools  
Large Spool: 10 spools

#### FOOTAGE/PALLET:

96,000 ft + 1000 - 0 ft  
120,000 ft + 1000 - 0 ft

#### FINISHED SPOOL UNIT WEIGHT:

~53 lbs  
~77 lbs

#### PACKAGING:

|              |              |                 |                    |
|--------------|--------------|-----------------|--------------------|
| Medium Spool | 15.49" width | 1.5" shaft O.D. | 19.75" flange O.D. |
| Large Spool  | 15.81" width | 1.5" shaft O.D. | 23.50" flange O.D. |

#### PROPERTIES:

Zipper material(s): Soft Seal® material with special sealant  
Suitable for food contact applications  
Sealing temperature range: \*\*200-280 °F  
Holding force from product side: 2.5 lbs target avg.

Each spool individually wrapped & placed in individual shipping case.

\*\*Temperature range may vary depending on type of package film used.

**Call your Fresh-Lock® zipper representative for details on our Zipper Spool Reuse Program.**

[www.Fresh-Lock.com](http://www.Fresh-Lock.com)



© 2011 Presto Products Company • A Business of Reynolds Packaging Group  
P.O. Box 2399 • Appleton, WI 54912-2399  
(800) 265-0750 • Fax (920) 738-1347 • E-mail: fresh-lock@reynoldspkg.com

