



Fresh-Lock® Style 206 Soft Seal® ME Zipper A Combination of Performance and Value

- Available in Presto's proprietary Soft Seal® material for a high-integrity side seal using less crushing energy.
- Requires less crushing time and/or temperature, allowing faster converting cycles
- Easy-to-crush material creates high-quality side seals that won't leak, gap or distort
- Versatile style works with vertical or horizontal form/fill/seal equipment or pre-formed pouches
- Improved seal integrity minimizes leakage
- Lower sealing temperatures reduce film distortion for improved package appearance
- Holding force is among the strongest of any FRESH-LOCK® zipper for maximum security
- Single-zipper channel snaps securely for tight seal

Locked and Loaded with Value, and offering improved package quality

Based on our most versatile zipper, Style 106, Style 206 works superbly on vertical or horizontal form/fill/seal equipment as well as pre-formed pouches. The superior holding force helps to prevent your package from opening under pressure. Soft Seal® material with special sealant layer enhances package quality.

Zipper Specification

Product Description: **STYLE 206 - Soft Seal® Material + ME Sealant**

GKL07434-1 Medium Reusable Spool
GKL07435-1 Large Reusable Spool

GKL07534-1 Medium Recyclable Spool
GKL07535-1 Large Recyclable Spool

PROFILE WEIGHT:

1.9 grams/ft +/- 0.1 grams/ft

WIDTH MEASUREMENTS:

10.3 mm +/- 0.3 mm

FOOTAGE/SPOOL:

Medium Spool: 10,000 ft + 100 - 0 ft
Large Spool: 20,000 ft + 100 - 0 ft

SPOOLS/PALLET:

Medium Spool: 12 spools
Large Spool: 10 spools

FOOTAGE/PALLET:

120,000 ft + 1000 - 0 ft
200,000 ft + 1000 - 0 ft

FINISHED SPOOL UNIT WEIGHT:

~47 lbs
~90 lbs

PACKAGING:

Medium Spool	15.49" width	1.5" shaft O.D.	19.75" flange O.D.
Large Spool	15.81" width	1.5" shaft O.D.	23.50" flange O.D.

PROPERTIES:

Zipper material(s): Soft Seal® material with special sealant
Suitable for food contact applications
Sealing temperature range: **200-280 °F
Holding force from product side: 3.0 lbs target avg.

POSITION OF ZIPPER:

The post next to interlocking members must be positioned toward the product/inside of package.

Each spool individually wrapped & placed in individual shipping case.

**Temperature range may vary depending on type of package film used.

Call your Fresh-Lock® zipper representative for details on our Zipper Spool Reuse Program.

www.Fresh-Lock.com



© 2008 Presto Products Company • A Business of Reynolds Packaging Group
P.O. Box 2399 • Appleton, WI 54912-2399
(800) 265-0750 • Fax (920) 738-1347 • E-mail: fresh-lock@reynoldspkg.com

