



## Fresh-Lock® Style 290 Soft Seal® ME A Solid Performer

- Available in Presto's proprietary Soft Seal® material for a high-integrity side seal using less crushing energy
- The FRESH-LOCK® Color Reveal™ zipper lets you know the bag is closed. Colors can be customized.
- Coextruded profile features a solid layer of a special sealant for enhanced sealability of zipper to film
- Improved seal integrity minimizes leakage
- Lower sealing temperatures reduce film distortion for improved package appearance
- Sealant layer provides good sealability to a wide variety of films
- Engineered for horizontal form/fill/seal equipment or preformed pouches
- Substantial multi-track locking channel allows consumers to feel the zipper closing through the packaging film and snaps securely for tight seal

### Closing Action You Can Feel and Loaded with Value

The design of the FRESH-LOCK® Style 290 zipper allows consumers to feel the closing action when resealing your package. Style 290 has a multi-track locking channel which is easy to open yet helps to prevent your package from opening under pressure. This zipper style not only seals at lower temperatures for faster line speeds, it also seals to thinner films and reduces leaker rates. Add value and convenience to your product packaging.

## Zipper Specification

### Product Description: STYLE 290

**GKL07444-1 Clear Medium Reusable Spool**  
**GKL07443-1 Medium Reusable Spool**  
White/Blue Color Reveal™

**GKL07544-1 Clear Medium Recyclable Spool**  
**GKL07543-1 Medium Recyclable Spool**  
White/Blue Color Reveal™

#### PROFILE WEIGHT:

1.8 grams/ft +/- 0.1 grams/ft

#### WIDTH MEASUREMENTS:

12 mm +/- 0.5 mm

#### FOOTAGE/SPOOL:

11,000 ft + 100 - 0 ft

#### SPOOLS/PALLET:

12 spools

#### FOOTAGE/PALLET:

132,000 ft + 1000 - 0 ft

#### FINISHED SPOOL UNIT WEIGHT:

~49 lbs

#### PACKAGING:

Medium Spool      15.49" width  
                                 1.5" shaft O.D.  
                                 19.75" flange O.D.

#### PROPERTIES:

Zipper material(s): Soft Seal® material with special sealant layer  
Suitable for food contact applications  
Sealing temperature range: \*\*200-280 °F  
Holding force from product side: 1.7 lbs target avg.  
Each spool individually wrapped & placed in individual shipping case.

#### POSITION OF ZIPPER:

The post next to interlocking members must be positioned toward the product/inside of package.

\*\*Temperature range may vary depending on type of package film used.

**Call your Fresh-Lock® zipper representative for details on our Zipper Spool Reuse Program.**

[www.Fresh-Lock.com](http://www.Fresh-Lock.com)



© 2008 Presto Products Company • A Business of Reynolds Packaging Group  
P.O. Box 2399 • Appleton, WI 54912-2399  
(800) 265-0750 • Fax (920) 738-1347 • E-mail: fresh-lock@reynoldspkg.com

