



FRESH-LOCK® Style 341 Soft Seal® ME Zipper Contaminate-Resistant Zipper

- Presto's proprietary Soft Seal® material requires less crushing energy
- Innovative zipper design offers convenience and performance for packaging dry, powdered, or granular products
- Reconfigured male and female closures channel particles outward and away from the zipper track
- Flat interior traps and holds stray material away from the locking mechanisms for smooth, clean zipper performance
- Tight, dependable seal locks in product content and hinders spillage
- Low seal temperature reduces film distortion, provides maximum performance
- Ribbed sealant allow lower sealing temperatures to a wide variety of films

No More Nitty-Gritty Closure Problems

Now even hard-to-hold powdered or granular products can be packaged with reclosable zippers the convenience feature many consumers prefer! Our proprietary design keeps particles from interfering with the zipper tracks for a tight, worry-free close. No mess. No clogging. Just smooth, easy performance.

Profitable Opportunities for Powdered or Granular Products

Style 341's contaminate-resistant technology opens new opportunities for a wide range of applications, including: powdered drink mixes; sugar, flour and baking ingredients; spices; sauce mixes; cereals and snacks; birdseed and pet foods; detergents and cleaning powders; even fertilizers and potting soil. Imagine the profitable possibilities at point of sale!

Zipper Specification

Product Description: STYLE 341 - Soft Seal® Material + ME Sealant Ribs

GKL07465-1 Large Reusable Spool

GKL07565-1 Large Recyclable Spool

PROFILE WEIGHT:

3.20 grams/ft +/- 0.1 grams/ft

WIDTH MEASUREMENTS:

20.00 mm +/- 1.0 mm

FOOTAGE/SPOOL:

8,000 ft + 100 - 0 ft

SPOOLS/PALLET:

10 spools

FOOTAGE/PALLET:

80,000 ft + 1000 - 0 ft

FINISHED SPOOL UNIT WEIGHT:

~66.4 lbs

PACKAGING:

Large Spool 15.81" width
 1.5" shaft O.D.
 23.5" flange O.D.

PROPERTIES:

Zipper material(s): LDPE blend with adhesive sealant layer
Suitable for food contact applications
Sealing temperature range: **200-280 °F
Holding force from product side: 4.25 lbs target avg.

Each spool individually wrapped & placed in individual shipping case.

**Temperature range may vary depending on type of package film used.

Call your Fresh-Lock® zipper representative for details on our Zipper Spool Reuse Program.

www.Fresh-Lock.com



© 2011 Presto Products Company • A Business of Reynolds Packaging Group
P.O. Box 2399 • Appleton, WI 54912-2399
(800) 265-0750 • Fax (920) 738-1347 • E-mail: fresh-lock@reynoldspkg.com

