



Fresh Technology

FRESH-LOCK® Style 346 ME Transverse Zipper Technology

- Style 346 ME brings FRESH-LOCK® zipper quality and performance to pre-zipped film stock
- Creates zippered packaging without in-line zipper application
- Exclusively designed for the INNO-LOK® System from The Hudson-Sharp Machine Company
- Features easy, reliable open and reclose
- Applied across the film web and delivered to the packaging machine as process-ready roll stock
- Allows use of zipper technology with little or no machine modification
- Eliminates leaks or film distortion at the side seal, since zipper does not enter seal area
- Works seamlessly with vertical form/fill/seal processes
- Requires no extra set-up time or reduction in cycle rates

Performance Across the Package

Now packagers who want the convenience of a reclosable package without the requirements of in-line zipper application have a premium choice: Style 346 ME FRESH-LOCK® zipper made exclusively for the INNO-LOK® Pre-Zipped Film System from The Hudson-Sharp Machine Company.

Style 346 ME FRESH-LOCK® zipper is tested and proven to deliver top performance on the INNO-LOK® System, plus has the easy open and reclose features consumers prefer.

ZIPPER SPECIFICATION

Product Description: STYLE 346 ME - INNO-LOK®

Product Code: **GKL07362-1 6,000' / Spool**
GKL07363-1 20,000' / Spool

PROFILE WEIGHT:

4.37 grams/ft +/- 0.17 grams/ft

WIDTH MEASUREMENTS:

42 mm +/- 1.0 mm

FOOTAGE / SPOOL:

6,000 ft + 100 - 0 ft
20,000 ft + 100 - 0 ft

SPOOLS / PALLET:

10 spools
2 spools

FOOTAGE/PALLET:

60,000 ft + 1000 - 0 ft
40,000 ft + 200 - 0 ft

FINISHED SPOOL

UNIT WEIGHT:

~ 76.3 lbs
~211.7 lbs

PACKAGING:

Spools: 14" core length
1.5" shaft O.D.
23.5" flange O.D.

19" core length
2" shaft O.D.
32.5" flange O.D.

PROPERTIES:

Zipper material(s): LDPE blend with special sealant layer
Suitable for food contact applications
Sealing temperature range: ** 200-280 °F
Holding force from product side: 6.0 lbs target avg.

Each spool individually wrapped & placed in individual shipping case **Temperature range may vary depending on type of package film used.

Call your **FRESH-LOCK®** zipper representative to lock in convenience and consumer appeal on your next packaging project.

